

ADVANTEK® 40xW SERIES (NARROW RIM, WEATHERIZED)



RATING
 For no rating, leave blank
H Hurricane
F Fire Rated (Less/No Dogging Only)
FH Hurricane and Fire Rated

OUTSIDE TRIM / DEVICE FINISH
605 Polished brass (PVD)
606 Brushed brass (PVD)
611 Polished bronze (PVD)
612 Brushed bronze (PVD)
613 Oil rubbed bronze
625 Polished chrome
626 Brushed chrome (std. on lever trims)
628 Aluminum, powder coated (device only)
629 Polished stainless steel
630 Brushed stainless steel (std. on pull trims & device)
693 Black, powder coated
695 Dark bronze, powder coated

DOGGING FUNCTION
LD Less/No dogging
HD Hex key dogging
CD Cylinder key dogging

PRE-INSTALLED CYLINDERS
 If cylinders provided by others, leave blank
MC65 Mortise Cylinder(s) 6pin/Keyed 5
IC7 Mortise Cylinder(s) SFIC housing
IK7 Mortise Cylinder(s) InstaKey housing
RC65 Rim Cylinder(s) 6pin/Keyed 5
IC7R Rim Cylinder(s) SFIC housing
IK7R Rim Cylinder(s) InstaKey housing

ENDCAP
EC1 Ramped endcap*
EC2 Flush endcap

FASTENERS
 For standard machine, wood & self-drilling screws, leave blank
SN1 Sex Nuts/Throughbolts (Hurricane rated hardware includes sex nuts for latch bolt)

KNURLING
 For no knurling, leave blank
KN Knurled (lever trim only)

SERIES TYPE
40xW Weatherized Rim device, narrow stile (non-electrified)

STRIKES
98 Semi-Mortise*
99 Surface


Specify KA for Keyed Alike

ANTIMICROBIAL
 For no coating, leave blank
AM Antimicrobial Coating

Trim Device

Trim

Device



OUTSIDE TRIM FUNCTION
 For no outside trim, leave blank
01CN Exit only, blank plate
02CN Dummy pull trim
03CN Key retracts latch; pull trim
03WS Key retracts latch; plate - short
01DN Blank escutcheon; Narrow lever handle (handed) (J, Q, S, T, U or FSB1076 lever)**
02DN Dummy lever trim
08DN Active lever, key locks / unlocks lever; Narrow lever handle (handed) (J, Q, S, T, U or FSB1076 lever**) (classroom)
09DN Lever trim active by key, locked when key removed; Narrow lever handle (handed) (J, Q, S, T, U or FSB1076 lever**) (storeroom)
14DN Active lever, no key cylinder; Narrow lever handle (handed) (J, Q, S, T, U or FSB1076 lever**) (passage)
CBK Cylinder bracket kit, 03 only, plate & pull handle by others required
EU2W Electric Unlock Trim (24VDC & Fail Secure [FSE] Std.) - Specify handing (not field reversible). For 12VDC specify 12VDC. For Fail Safe specify FSA.

DOOR HANDING
RHR Right hand reverse*
LHR Left hand reverse

KEYSTOP
 For no keystone, leave blank
KS Keystop (Available with EB W function)

DOOR WIDTH
24" wide door
30" wide door
36" wide door (3')*
48" wide door (4')

SILENCER
 For standard pushpad, leave blank
SLR Silent Latch & Pushpad

ELECTRIFIED FUNCTION

For no electrified function, leave blank

Weatherized Alarms
 Select Arming Time and Auto Rearm
EB W Electric Battery Operated Exit Alarm Weatherized
EB EX W Electric Battery Operated Exit Alarm Weatherized with Request To Exit (Signal) Switch
EB EXV W Electric Battery Operated Exit Alarm Weatherized with Request To Exit (3Amp Current) Switch

Weatherized Others
EX W Request To Exit (Signal) Switch Weatherized
EXV W Request To Exit Switch Weatherized (3 Amp Current)
WDE Weatherized Delayed Egress (see EasyKits)

POWER TRANSFERS
 For no power transfers, leave blank
FC3W 3' Weatherized Flex Conduit
FC10W 10' Weatherized Flex Conduit


Latch Retraction
ER EX W Electric Latch Retraction Weatherized with Request To Exit Switch (silencer std. on devices 36" and longer)

Power Supply / Controller for Latch Retraction Only (ER EX W)
 Order/Sold Separately
Single 81-800
Pair 82-800
2 Independent Singles 83-800

Fire-rated trims must be fail safe (FSA)

For EU (Electric Unlock Trim), see Outside Trim Function -

**Other FSB levers available: 1016, 1035, 1058, 1075, 1093, 1119, 1147. FSB levers available in 630 finish only. See catalog pages for more information.



NOTE: * default/standard

Also see online version at detex.com/hto

June 13, 2022