ADVANTEX® 50xW/51xW SERIES (NARROW SURFACE VERTICAL ROD, WEATHERIZED)

RATING
For no rating, leave blank
H Hurricane Rated
F Fire Rated (Less/No Dogging Only) - Fire pin included for F51
FH Hurricane and Fire Rated

KNURLING
For no knurling, leave blank
KN Knurled (lever trim only)

SERIES TYPE
50xW Weatherized SVR, narrow stile (non-electrified)
51xW Weatherized SVR, top rod only, narrow stile (non-electrified)

OUTSIDE TRIM / DEVICE FINISH
605 Polished brass (PVD)
606 Brushed brass (PVD)
611 Polished bronze (PVD)
612 Brushed bronze (PVD)
613 Oil rubbed bronze
625 Polished chrome
626 Brushed chrome (std. on lever trims)
628 Aluminum, powder coated (device only)
629 Polished stainless steel
630 Brushed stainless steel (std. on pull trims & device)
693 Black, powder coated
695 Dark bronze, powder coated

Trim | Device

DOGGING FUNCTION
LD Less/No dogging
HD Hex key dogging
CD Cylinder key dogging

STRIKES
96 Surface

PRE-INSTALLED CYLINDERS
If cylinders provided by others, leave blank
MC65 Mortise Cylinder(s) 6pin/Keyed 5
IC7 Mortise Cylinder(s) SFIC housing
IK7 Mortise Cylinder(s) InstaKey housing
RC65 Rim Cylinder(s) 6pin/Keyed 5
IC7R Rim Cylinder(s) SFIC housing
IK7R Rim Cylinder(s) InstaKey housing

Specify KA for Keyed Alike

Trim | Device

DOOR HEIGHT/SVR HEIGHT
For 84" door heights, leave blank
84" high door
96" high door
120" high door

ENDCAP
EC1 Ramped endcap*
EC2 Flush endcap

FASTENERS
For standard machine, wood & self-drilling screws, leave blank
SN1 Sex Nuts/Throughbolts

OUTSIDE TRIM FUNCTION
For no outside trim, leave blank
01CN Exit only, blank plate
02CN Dummy pull trim
03CN Key retracts latch; pull trim
03WS Key retracts latch; plate - short
01DN Blank escutcheon; Narrow lever handle (handed) (J, Q, S, T, U or FSB1076 lever)**
02DN Dummy lever trim
08DN Active lever, key locks / unlocks lever; Narrow lever handle (handed) (J, Q, S, T, U or FSB1076 lever**) (classroom)
09DN Lever trim active by key, locked when key removed; Narrow lever handle (handed) (J, Q, S, T, U or FSB1076 lever**) (storeroom)
14DN Active lever, no key cylinder; Narrow lever handle (handed) (J, Q, S, T, U or FSB1076 lever**) (passage)
CBK Cylinder bracket kit, 03 only, plate & pull handle by others required
EU2W Electric Unlock Trim (24VDC & Fail Secure [FSE] Std.) - Specify handing (not field reversible). For 12VDC specify 12VDC. For Fail Safe specify FSA.

DOOR HANDING
RHR Right hand reverse*
LHR Left hand reverse

KEYSTOP
For no keystop, leave blank
KS Keystop (Available with EB W function)

DOOR WIDTH
24" wide door
30" wide door
36" wide door (3')*
48" wide door (4')

ANTIMICROBIAL
For no coating, leave blank
AM Antimicrobial Coating

SILENCER
For standard pushpad, leave blank
SLR Silent Latch & Pushpad

ELECTRIFIED FUNCTION

For no electrified function, leave blank

Weatherized Alarms
Select Arming Time and Auto Rearm
EB W Electric Battery Operated Exit Alarm Weatherized
EB EX W Electric Battery Operated Exit Alarm Weatherized with Request To Exit (Signal) Switch
EB EXV W Electric Battery Operated Exit Alarm Weatherized with Request To Exit Switch (3 Amp Current)

Latch Retraction
ER EX W Electric Latch Retraction Weatherized with Request To Exit Switch (silencer std. on devices 36" and longer)

Weatherized Others
EX W Request To Exit (Signal) Switch Weatherized
EXV W Request To Exit Switch Weatherized (3 Amp Current)
WDE Weatherized Delayed Egress (see EasyKits)

POWER TRANSFERS
For no power transfers, leave blank
FC3W 3' Weatherized Flex Conduit
FC10W 10' Weatherized Flex Conduit

Power Supply / Controller for Latch Retraction Only (ER EX W)
Order/Sold Separately
Single 81-800
Pair 82-800
2 Independent Singles 83-800

Fire-rated trims must be fail safe (FSA)

**Other FSB levers available: 1016, 1035, 1058, 1075, 1093, 1119, 1147. FSB levers available in 630 finish only.See catalog pages for more information.

Detex products can expose you to chemicals including Chromium (hexavalent compounds) and Lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.detex.com/prop65

NOTE: * default/standard

Also see online version at detex.com/hto

June 13, 2022